

AK COMPACTOR SERIES

GRADES: 32,46,68,100,150,220,320

DESCRIPTION:

AUTOKING COMPACTOR SERIES Oils are manufactured from highly refined base stock with oxidation, rust, corrosion and Foam inhibitors. These oils provides excellent lubrication under high temperature and high load conditions as well as give excellent resistance to washing effect of water and provide superior thermal stability.

AUTOKING COMPACTOR SERIES Oils have good Demulsibility, low sludge and deposit and exceptional resistance to oxidation and thermal degradation.

APPLICATION:

- AK COMPACTOR SERIES Oils are recommended for use in cylindrical lubricants of reciprocating and rotary air compressor, also suitable for critical gears and bearing systems compressor.
- AK COMPACTOR SERIES Oils are recommended for compressor used in stationary and mobile applications.

PERFORMANCE LEVEL:

- DIN:51506-SPECIFICATIONS
- IS: 13256-1992.
- ISO: 6521.

FEATURES

- Excellent oxidation & thermal stability.
- Low ash carbon formulation.
- Superb rust and corrosion protection.

BENEFITS:

- Enable trouble free starting of low temperature.
- Reduce oil consumption.

TYPICAL PROPERTIES:

CHARACTERSTICS	32	46	68	100	150	220	320
ISO GRADE	32	46	68	100	150	220	320
DENSITY@15°C	0.84-0.86	0.84-0.86	0.84-0.86	0.85-0.87	0.85-0.87	0.86-0.89	0.86-0.89
KINEMATIC VISCOSITY@40°C, CST	29-35	42-49	62-73	90-110	140-160	200-240	290-340
VISCOSITY INDEX, MIN.	100	100	100	100	100	100	100
FLASH POINT°C, MIN.	210	210	220	220	220	220	220
POUR POINT°C, MAX.	-9	-9	-9	-9	-9	-9	-9
RUST TEST	PASS						

HEALTHY, SAFETY &ENVIRONMENT:- Auto king oil are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standard of industrial and personal hygiene are maintained. For more details contact STERLITE INDIA REPRESENTATIVES.

STERLITE LUBRICANTS PVT. LTD.
Corporate Headquarters
65-Second Floor, 4D SQUARE,
Visat-Ghandhinagar Highway,
Motera, Ahmedabad 380005
079-66172662 | www.sterlitelubricants.com
Make in India | All rights reserved.

©2005 Sterlite Lubricants Pvt. Ltd.

Disclaimer

"Autoking" and "Oils by an Indian" are intended and authorized for use only in countries and jurisdiction in which Autoking has obtained the rights to use, market and advertise the brand. Autoking shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Autoking products or services do not imply that Autoking intends to make these available in all countries in which it operates. Contact SLPL for more information or mail to info@sterlitelubricants.com.