

# **AK DEO EXPRESS 15W40 CH4**

#### **DESCRIPTION:**

AUTOKING DEO EXPRESS 15W40 CH-4 is Multipurpose Premium Quality diesel engine oil. AK DEO 15W40 CH-4 Oil is designed for most severe performance requirement of new generation commercial vehicles for on highway and off highway operation .lt requirement of engine complying with EURO-III.

AUTOKING DEO EXPRESS 15W40 CH-4 is specially compounded for use with diesel fuel ranging in sulphur contain up to 0.3% offers better thermal and oxidation stability controls sludge build-up and deposits. Also Shear stability stay in grade, protection from wear and reduced oil consumption.

## **APPLICATION:**

AK DEO EXPRESS 15W 40 CH-4 is recommended for new generation commercial diesel vehicles' for on highway and off-highway operation. It also recommended for construction, mining, quarrying and agriculture.

### **PERFORMANCE LEVEL:**

- API-CH-4 & IS 13656:2002,
- ACEA E3-96, MB 228.3, MAN-3275,
- Volvo VDS-2, Cummins CES-20076
- MACK EO-M Plus

#### **PERFORMANCE:**

- Excellent engine cleanliness due to better detergency.
- Catalytic convertor compatible.
- Reduced engine scuffing and bore polishing.
- Suitable for mixed fleet operation.

### **BENEFITS:**

- Minimize deposits, resulting from high output, low speed and low temperature operation.
- Maintain excellent engine cleanliness & Provide excellent control of corrosive wear.

### **TYPICAL PROPERTIES:**

| CHARACTERISTICS                 | DEO EXPRESS 15W40 CH-4 |
|---------------------------------|------------------------|
| KINEMATIC VISCOSITY @100°C, CST | 14 - 15                |
| VISCOSITY INDEX, MIN.           | 135 - 145              |
| FLASH POINT °C, MIN.            | 234                    |
| POUR POINT °C, MAX.             | -15                    |
| TBN (MG KOH/GM)                 | 9.5 - 11.5             |

**HEALTHY, SAFETY & ENVIRONMENT:-** Auto king oil are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standard of industrial and personal hygiene are maintained. For more details contact STERLITE INDIA REPRESENTATIVES.

STERLITE LUBRICANTS PVT. LTD.
Corporate Headquarters
65-Second Floor, 4D SQUARE,
Visat-Ghandhinagar Highway,
Motera, Ahmedabad 380005
079-66172662 | www.sterlitelubricants.com
Make in India | All rights reserved.

©2005 Sterlite Lubricants Pvt. Ltd.

Disclaimer

"Autoking" and "Oils by an Indian" are intended and authorized for use only in countries and jurisdiction in which Autoking has obtained the rights to use, market and advertise the brand. Autoking shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Autoking products or services do not imply that Autoking intends to make these available in all countries in which it operates. Contact SLPL for more information or mail to info@sterlitelubricants.com.

## PRODUCT DATA SHEET



STERLITE LUBRICANTS PVT. LTD.
Corporate Headquarters
65-Second Floor, 4D SQUARE,
Visat-Ghandhinagar Highway,
Motera, Ahmedabad 380005
079-66172662 | www.sterlitelubricants.com
Make in India | All rights reserved.

©2005 Sterlite Lubricants Pvt. Ltd.

#### Disclaimer

"Autoking" and "Oils by an Indian" are intended and authorized for use only in countries and jurisdiction in which Autoking has obtained the rights to use, market and advertise the brand. Autoking shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Autoking products or services do not imply that Autoking intends to make these available in all countries in which it operates. Contact SLPL for more information or mail to info@sterlitelubricants.com.