



## AUTOKING AK-LR 40000 GREASE

### DESCRIPTION:

AUTOKING AK-LR 40000 Grease is formulated with specially selected additives to provide excellent oxidation stability.

AUTOKING AK-LR 40000 Grease also contains antioxidants, anti-corrosion and extreme pressure additives for enhanced extreme Pressure and anti-seize performance. It exhibits good water resistance and excellent adherence to metal surfaces. Provides protection against fretting corrosion, typically associated with spline shafts, pivot pins, constant viscosity joints.

### APPLICATION:

- AUTOKING AK-LR 40000 grease is used in a wide range of equipment including industrial, automotive, construction and marine applications. Their blue color enables easy verification of application
- AUTOKING AK-LR 40000 grease is also suitable for applications where good high temperature and anti-leakage properties are required. It is particularly recommended for severe truck wheel bearing applications or for rolling element bearings subject to vibration, or where higher speeds require.

### PERFORMANCE LEVEL:

- Proprietary Grease.

### PERFORMANCE

- Superb resistance to water washout.
- Highly adhesive and cohesive structure.
- Very good anti-wear and EP performance.
- Excellent rust and corrosion resistance.

### BENEFITS:

- Excellent grease tendency helps reduce leakage and extend re-lubrication intervals.
- Provides Superior Equipment protection under boundary lubrication conditions.
- Superior oxidation stability and corrosion control.
- Excellent anti-wear and water resistance properties.
- Wide operating temperature range up to 160°C.
- Higher consistency to provide channeling characteristics.



**TYPICAL PROPERTIES:**

<b>CHARACTERSTICS</b>	<b>AK-LR 40000 GREASE</b>
NLGI GRADE	2
COLOUR	DARK BLUE
THICKENER TYPE	LITHIUM COMPLEX
WORKING PREPRATION @25 <sup>0</sup> C, 60/60 STROKES	265 - 295
DROPPING POINT <sup>0</sup> C, MIN.	>265
FOUR BALL WELD LOAD, KGF	315
FOUR BALL WEAR SCAR TEST, dia in mm.	0.5
TIMKEN OK LOAD	40
ENCOR RUST PROTECTION TEST	0,0
WATERWASH OUT, 80 C, % loss.	4.0 max.
BASE OIL VISCOSITY, CST	220

HEALTHY & SAFETY ENVIRONMENT: - Auto king oil are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standard of industrial and personal hygiene are maintained. For more details contact STERLITE INDIA REPRESENTATIVE

## PRODUCT DATA SHEET



*Oils by an Indian*

STERLITE LUBRICANTS PVT. LTD.  
Corporate Headquarters  
65-Second Floor, 4D SQUARE,  
Visat-Gandhinagar Highway,  
Motera, Ahmedabad 380005  
079-66172662 | [www.sterlitolubricants.com](http://www.sterlitolubricants.com)  
Make in India | All rights reserved.

©2005 Sterlite Lubricants Pvt. Ltd.

### Disclaimer

"Autoking" and "Oils by an Indian" are intended and authorized for use only in countries and jurisdiction in which Autoking has obtained the rights to use, market and advertise the brand. Autoking shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Autoking products or services do not imply that Autoking intends to make these available in all countries in which it operates. Contact SLPL for more information or mail to [info@sterlitolubricants.com](mailto:info@sterlitolubricants.com).