



AK RUBBSTER PRP SERIES (PARAFFINIC BASE RUBBER PROCESSING OILS)

GRADE: PRP-1 , PRP-2

DESCRIPTION:

AUTOKING RUBBSTER PRP-1 and PRP-2 are Paraffinic type of Oil having Moderate Viscosity and flash point. These oils are formulated from highly refined solvent extracted base stocks with low Sulphur content.

AUTOKING RUBBSTER PRP-1 and PRP-2 Oils are used in Manufacturing of butyl tubes and a variety of technical Molded and Extruded products based on Polar Rubbers like EPM & EPDM etc. These oils have light Colour.

APPLICATION:

- AK RUBBSTER PRP-1 and PRP-2 Oils are recommended for light-colored rubber goods like TPR foot wears, Rubber seal, Gasket, Hot Water bottles, Conveyor Belts Radiators & Steam Hose Pipe.
- Colour less, Test less, White petroleum jelly recommended in manufacturing of rubber goods which are hygienic in nature.

PERFORMANCE LEVEL:

- ASTM 104 Type

PERFORMANCE

- Good Thermal, Oxidation and Colour Stability
- Improves ageing properties of rubber articles.
- Improves tear and elongation strength of the finish rubber goods.

BENEFITS:

- Suitable for heat resistance conveyor belts and Stream hoses
- Reduce compounding time
- Low Sulphur Content
- Compatible with PBR
- Better extrusion due to the lubricating action
- Low Heat Buildup Properties.

TYPICAL PROPERTIES:

CHARACTERISTICS	PRP-1	PRP-2
APPEARANCES	CLEAR	CLEAR
KINEMATIC VISCOSITY@40°C, CST	28-35	420-480
FLASH POINT °C, MIN.	210	250
ANILINE POINT °C	90-100	100-120
POUR POINT °C, MAX.	-6	-3
ACID VALUE (MG KOG/GM)	0.1 MAX	0.1 MAX

HEALTHY, SAFETY & ENVIRONMENT:- Auto king oil are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standard of industrial and personal hygiene are maintained. For more details contact STERLITE INDIA REPRESENTATIVES.

STERLITE LUBRICANTS PVT. LTD.
Corporate Headquarters
65-Second Floor, 4D SQUARE,
Visat-Ghandhinagar Highway,
Motera, Ahmedabad 380005
079-66172662 | www.sterlitelubricants.com
Make in India | All rights reserved.

©2005 Sterlite Lubricants Pvt. Ltd.

Disclaimer

“Autoking” and “Oils by an Indian” are intended and authorized for use only in countries and jurisdiction in which Autoking has obtained the rights to use, market and advertise the brand. Autoking shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Autoking products or services do not imply that Autoking intends to make these available in all countries in which it operates. Contact SLPL for more information or mail to info@sterlitelubricants.com.