

AK TRACK UTTO 80W

DESCRIPTION:

AUTOKING TRACK UTTO 80W oil suitable for use in most agricultural tractors and associated equipment. Inhibitors are incorporated to ensure excellent corrosion protection, reduced gear wear, and freedom from foaming. Friction modifiers are used to eliminate brake squawk on machines fitted with oil immersed brakes.

APPLICATION:

- Suitable for all new generation tractors having oilimmersed brakes.
- Recommended to meet the requirements of Swaraj and Mahindra and Mahindra tractors.

PERFORMANCE LEVEL:

- JOHN DEERE JDM J20C, FORD M2C 134D,
- MESSY FERGUSON M1141 & M1145.
- CASE MS 1207/1209, KOMATSU AXO 80.

PERFORMANCE

- Superior protection against rust & corrosion.
- Provides excellent lubrication for gear box.
- Balanced lubricity and other functional properties

BENEFITS:

- Ensures noise-free operation of immersed brakes with its friction modifier technology
- Ensures longer transmission life.
- Protects against rust and corrosion.
- Increases oiliness for effective braking.

TYPICAL PROPERTIES:

CHARACTERISTICS	AK TRACK UTTO 80W
Kinematic Viscosity, cst @ 100° C	9.5 - 12
Viscosity Index, min.	100
Pour Point, °C, maxes.	-15
Flash Point, COC, °C, min.	200
Total Base Number, mg KOH /gm	3.5 – 4.5

HEALTHY, SAFETY &ENVIRONMENT:- Auto king oil are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standard of industrial and personal hygiene are maintained. For more details contact STERLITE INDIA REPRESENTATIVES.

STERLITE LUBRICANTS PVT. LTD.
Corporate Headquarters
65-Second Floor, 4D SQUARE,
Visat-Ghandhinagar Highway,
Motera, Ahmedabad 380005
079-66172662 | www.sterlitelubricants.com
Make in India | All rights reserved.

©2005 Sterlite Lubricants Pvt. Ltd.

Disclaimer

"Autoking" and "Oils by an Indian" are intended and authorized for use only in countries and jurisdiction in which Autoking has obtained the rights to use, market and advertise the brand. Autoking shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Autoking products or services do not imply that Autoking intends to make these available in all countries in which it operates. Contact SLPL for more information or mail to info@sterlitelubricants.com.

PRODUCT DATA SHEET



STERLITE LUBRICANTS PVT. LTD.
Corporate Headquarters
65-Second Floor, 4D SQUARE,
Visat-Ghandhinagar Highway,
Motera, Ahmedabad 380005
079-66172662 | www.sterlitelubricants.com
Make in India | All rights reserved.

©2005 Sterlite Lubricants Pvt. Ltd.

Disclaimer

"Autoking" and "Oils by an Indian" are intended and authorized for use only in countries and jurisdiction in which Autoking has obtained the rights to use, market and advertise the brand. Autoking shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Autoking products or services do not imply that Autoking intends to make these available in all countries in which it operates. Contact SLPL for more information or mail to info@sterlitelubricants.com.