



AK DEO GUARD 15W40 CI4 PLUS

DESCRIPTION:

AUTOKING DEO GUARD 15W40 CI4 Plus is Premium multipurpose extra high performance diesel engine oil that provides excellent lubrication of latest version diesel engines promoting extended life. This extra high performance has been proven in the field in a wide variety of industries application.

AUTOKING DEO GUARD 15W40 CI4 Plus assures outstanding protection against high Temperature engine deposits, oil degradation, and oil thickening and corrosion resistance. It exhibits outstanding control on soot induced thickening and soot induced wear.

APPLICATION:

- AK DEO GUARD 15W40 CI-4 Plus is best recommended for use in on highway light and heavy duty tracking, off-highway industries including construction, mining, quarrying and agriculture. Also recommend for turbo-charged diesel powered equipment.

TYPICAL PROPERTIES:

CHARACTERISTICS	DEO GUARD 15W40 CI-4 PLUS
KINEMATIC VISCOSITY @ 100°C, CST	14 - 15
VISCOSITY INDEX, MIN.	130 - 140
FLASH POINT °C, MIN.	225
POUR POINT °C, MAX.	-35
TBN (MG KOH/GM)	10 - 12

HEALTHY, SAFETY & ENVIRONMENT:- Auto king oil are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standard of industrial and personal hygiene are maintained. For more details contact STERLITE INDIA REPRESENTATIVES.

STERLITE LUBRICANTS PVT. LTD.
 Corporate Headquarters
 65-Second Floor, 4D SQUARE,
 Visat-Gandhinagar Highway,
 Motera, Ahmedabad 380005
 079-66172662 | www.sterlitelubricants.com
 Make in India | All rights reserved.

©2005 Sterlite Lubricants Pvt. Ltd.

Disclaimer

"Autoking" and "Oils by an Indian" are intended and authorized for use only in countries and jurisdiction in which Autoking has obtained the rights to use, market and advertise the brand. Autoking shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Autoking products or services do not imply that Autoking intends to make these available in all countries in which it operates. Contact SLPL for more information or mail to info@sterlitelubricants.com.

PERFORMANCE LEVEL:

- API CI-4 Plus
- ACEA E7
- Caterpillar ECF 2
- MACK EON PP - 03
- MB 228.3 & VOLVO VDS-3.

PERFORMANCE

- Easier cold starting.
- High engine cleanliness.
- Better thermal and oxidation stability.

BENEFITS:

- Optimum Engine Performance
- Shear stability stay- in-grade, protection from wear and reduced oil consumption
- Reduced engine scuffing and bore polishing.



STERLITE LUBRICANTS PVT. LTD.
Corporate Headquarters
65-Second Floor, 4D SQUARE,
Visat-Gandhinagar Highway,
Motera, Ahmedabad 380005
079-66172662 | www.sterlitelubricants.com
Make in India | All rights reserved.

©2005 Sterlite Lubricants Pvt. Ltd.

Disclaimer

"Autoking" and "Oils by an Indian" are intended and authorized for use only in countries and jurisdiction in which Autoking has obtained the rights to use, market and advertise the brand. Autoking shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Autoking products or services do not imply that Autoking intends to make these available in all countries in which it operates. Contact SLPL for more information or mail to info@sterlitelubricants.com.

PRODUCT DATA SHEET



STERLITE LUBRICANTS PVT. LTD.
Corporate Headquarters
65-Second Floor, 4D SQUARE,
Visat-Gandhinagar Highway,
Motera, Ahmedabad 380005
079-66172662 | www.sterlitelubricants.com
Make in India | All rights reserved.

©2005 Sterlite Lubricants Pvt. Ltd.

Disclaimer

"Autoking" and "Oils by an Indian" are intended and authorized for use only in countries and jurisdiction in which Autoking has obtained the rights to use, market and advertise the brand. Autoking shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Autoking products or services do not imply that Autoking intends to make these available in all countries in which it operates. Contact SLPL for more information or mail to info@sterlitelubricants.com.