



## AK MEGALOOM SERIES

GRADE: 32,46,68,100,150,220,320,460

### DESCRIPTION:

AUTOKING MEGALOOM Series Oils Superb quality manufactured from Mineral oil and selected additives to provide good oiliness for general lubrication to machineries. AK MEGALOOM Series oils are designed to use for all loss lubrication system of looms and drives used in textile and jute mills.

AUTOKING MEGALOOM Series Oils maintain thin film of oil under light and medium load and provide protection against corrosion and rust even in ideal period. The inherent nature of oil has very low friction wear and also because of its anti-corrosive property, it extends the life of moving parts lubricated by oils.

### APPLICATION:

- AK MEGALOOM Series Oils are recommended for all type of industrial machinery including looms and other textile machinery.
- AK MEGALOOM Series Oils are also recommended for hand oiling application involving lubrication of bearing, open gears, lightly loaded slides and guide ways of machine tools.
- AK MEGALOOM Series Oils are also recommended for lubrication of non-critical all loss lubrication system of textile machinery, particularly the looms.

### PERFORMANCE LEVEL:

- IS: 493-part-I.1981 (RA-1998)

### PERFORMANCE

- Reduced maintenance costs and higher output due to longer oil change intervals

### BENEFITS:

- Excellent oxidation thermal stability
- Provide protection against rust and corrosion
- Excellent anti-wear properties
- Enhance lubrication by reducing friction



**TYPICAL PROPERTIES:**

CHARACTERISTICS	AK MEGALOOM							
ISO GRADE	32	46	68	100	150	220	320	460
APPEARANCES	CLEAR	CLEAR	CLEAR	CLEAR	CLEAR	CLEAR	CLEAR	CLEAR
KINEMATIC VISCOSITY @40°C, CST	30-35	40-50	64-72	90-110	140-160	200-240	300-340	420-480
KINEMATIC VISCOSITY @100°C, CST	5-7	6-9	8-11	10-14	12-18	18-22	20-25	28-35
VISCOSITY INDEX MIN.	90	90	90	90	90	90	90	90
FLASH POINT °C MIN.	200	200	210	210	220	220	220	220
POUR POINT °C MAX.	-9	-9	-9	-9	-6	-6	-6	-6

HEALTHY, SAFETY & ENVIRONMENT:- Auto king oil are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standard of industrial and personal hygiene are maintained. For more details contact STERLITE INDIA REPRESENTATIVES.

STERLITE LUBRICANTS PVT. LTD.  
 Corporate Headquarters  
 65-Second Floor, 4D SQUARE,  
 Visat-Ghandhinagar Highway,  
 Motera, Ahmedabad 380005  
 079-66172662 | www.sterlitolubricants.com  
 Make in India | All rights reserved.

©2005 Sterlite Lubricants Pvt. Ltd.

Disclaimer

"Autoking" and "Oils by an Indian" are intended and authorized for use only in countries and jurisdiction in which Autoking has obtained the rights to use, market and advertise the brand. Autoking shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Autoking products or services do not imply that Autoking intends to make these available in all countries in which it operates. Contact SLPL for more information or mail to info@sterlitolubricants.com.