



AK RUSTER CR

DESCRIPTION:

AUTOKING RUSTER CR Oil are low viscosity dewatering rust protective with ability to displace water from metallic surface, spreading rapidly to foam a rust preventing film at the same time.

AUTOKING RUSTER CR Oils contains oil soluble surface active agent dissolve in a solvent with suitable corrosion preventive and film forming materials. These oil can be applied at room temperature by dip or spray method.

APPLICATION:

AK RUSTER CR Oil is a multipurpose rust preventive providing medium term protection of ferrous and alloy components during storage and transit. It is also suitable for protection of highly machined precision parts where heavy film is not desirable.

PERFORMANCE LEVEL:

- BS: 7451-1992 Type TP2 (B).
- IS: 1154-2000.

FEATURES

- Improved coverage capacity, so that low consumption oil.
- Non-staining and are easily applicable by brush, spray or swab.

BENEFITS:

- Provide excellent rust protection to metal surface during storage.
- Thin, transparent robust films, so that easy to read marking on components.
- Superb dewatering and corrosion protection.

TYPICAL PROPERTIES:

| CHARACTERISTICS | CR 2 | CR 4 |
|--------------------------------|-------------|-------------|
| APPEARANCES | CLEAR | CLEAR |
| DENSITY @15°C | 0.86 - 0.89 | 0.86 - 0.89 |
| KINEMATIC VISCOSITY@ 40°C, CST | 1.4 - 1.8 | 3.5 - 4.5 |
| FLASH POINT °C, MIN. | 38 - 43 | 50 - 60 |
| FILM TYPE | DRY & SOFT | DRY & SOFT |
| FILM THICKNESS, MICRONS | 3.5 | 4.5 |
| WATER DISPLACEMENT PROPERTIES | PASS | PASS |

HEALTHY, SAFETY & ENVIRONMENT: - Auto king oil are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standard of industrial and personal hygiene are maintained. For more details contact **STERLITE INDIA REPRESENTATIVES**

STERLITE LUBRICANTS PVT. LTD.
 Corporate Headquarters
 65-Second Floor, 4D SQUARE,
 Visat-Gandhinagar Highway,
 Motera, Ahmedabad 380005
 079-66172662 | www.sterlitelubricants.com
 Make in India | All rights reserved.

©2005 Sterlite Lubricants Pvt. Ltd.

Disclaimer

"Autoking" and "Oils by an Indian" are intended and authorized for use only in countries and jurisdiction in which Autoking has obtained the rights to use, market and advertise the brand. Autoking shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Autoking products or services do not imply that Autoking intends to make these available in all countries in which it operates. Contact SLPL for more information or mail to info@sterlitelubricants.com.

PRODUCT DATA SHEET



STERLITE LUBRICANTS PVT. LTD.
Corporate Headquarters
65-Second Floor, 4D SQUARE,
Visat-Gandhinagar Highway,
Motera, Ahmedabad 380005
079-66172662 | www.sterlitelubricants.com
Make in India | All rights reserved.

©2005 Sterlite Lubricants Pvt. Ltd.

Disclaimer

"Autoking" and "Oils by an Indian" are intended and authorized for use only in countries and jurisdiction in which Autoking has obtained the rights to use, market and advertise the brand. Autoking shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks. References in this publication to Autoking products or services do not imply that Autoking intends to make these available in all countries in which it operates. Contact SLPL for more information or mail to info@sterlitelubricants.com.